

IT'S NOT A UTILITY VEHICLE.

IT'S A *Club Car*

 Ingersoll Rand



CAN A UTILITY VEHICLE REALLY DO THAT?

Brains and brawn. Now available in utility vehicles.

For all the advancements Club Car® has introduced to turf utility vehicles, the motivation comes down to one simple result: Work ethic. Vehicles that go where you need them to go, doing the jobs you need them to do, day in, day out, without problems. That's what led us to develop exclusives like all-aluminum frames that won't rust and are significantly stronger than

competitors' steel frames; the IQ Plus System™, a performance breakthrough for electronic drive trains; IntelliTrak™, a revolutionary all-wheel drive system that senses the terrain and automatically engages all four wheels as the conditions demand more power. And that's just the beginning. As long as courses put high demands on our vehicles, we'll keep innovating new ways to get the jobs done.

TURF 1



A versatile, multi-tasking machine that can out-manuever anything else in its class, the Carryall Turf 1 is up to any light-duty job you throw at it. Choose a gas engine or electric with Club Car's® exclusive IQ System™; either way, you have an energetic partner built for the long haul.

- Choice of 351 cc gasoline 11.5 hp engine or Club Car's exclusive IQ System 48-volt electric motor
- 800 lb (363.2 kg) Total Vehicle Capacity
- 9.1 ft³ (0.3 m³) Cargo Box carries 300 lb (136.1 kg)
- Radio/Beverage Holder
- Differential Guard
- Heavy Duty Front Bumper
- Battery warning light standard
- Rustproof Aircraft Grade Aluminum Frame, Chassis & Cargo Box
- Self-adjusting, maintenance-free rack & pinion steering for easy handling
- Premium tread tires
- Heavy duty unitized powertrain



TURF 2



When you want maneuverability with a little added muscle, the Carryall Turf 2 is your go-to guy. This economical yeoman is available in gas engine or electric with the IQ Plus System™, and can handle a variety of maintenance tasks, shouldering a full 1,200 pounds of vehicle capacity. Load it up, Turf 2 can take it.

- Choice of 351 cc gasoline 11.5 hp engine or Club Car's exclusive IQ Plus System 48-volt electric motor
- 1,200 lbs (544.8 kg) total vehicle capacity
- 15.3 ft³ (0.4 m³) Cargo Box carries 800 lb (363.2 kg)
- Headlights
- Radio/Beverage Holder
- Differential Guard
- Heavy Duty Front Bumper
- Battery warning light standard
- Rustproof Aircraft Grade Aluminum Frame, Chassis & Cargo Box
- Self-adjusting, maintenance-free rack & pinion steering for easy handling
- Premium tread tires
- Heavy duty unitized powertrain



TURF 6



It's all about return on investment these days and nothing fills that bill like the Carryall Turf 6. With 1,500 pounds of capacity and almost 6-feet of cargo bed, Turf 6 does it all. It's equipped with an 11.5 hp gas engine so you'll have all the power—and payload—you need for your operation's most demanding chores.

- 351 cc gasoline 11.5 hp engine
- 1,500 lbs (681 kg) total vehicle capacity with newly redesigned convenient under seat storage area
- 17.1 ft³ Cargo Box with flip-down tailgate
- Headlights
- Radio/Beverage Holder
- Differential Guard
- Heavy Duty Front Bumper
- Battery warning light standard
- Rustproof Aircraft Grade Aluminum Frame, Chassis & Cargo Box
- Self-adjusting, maintenance-free rack & pinion steering for easy handling
- Premium tread tires
- Hour meter
- Heavy duty unitized powertrain



TURF 252



If your to-do list is as long as your day, the rugged Carryall 252 with the IQ Plus System is the vehicle ready to go the distance. The high-output charger, controller, onboard computer and battery system give you fast charging and superior power and range. Prefer gas? There's an 11.5 hp, 351 cc gas engine that's primed to take on any challenge thrown its way.

- Choice of 351 cc gasoline 11.5 hp engine or Club Car's exclusive IQ Plus System 48-volt electric motor
- Headlights
- Radio/Beverage Holder
- Differential Guard
- Heavy Duty Front Brush Guard
- Battery warning light standard
- Rustproof Aircraft Grade Aluminum Frame, Chassis & Cargo Box
- Independent front suspension
- Rear suspension with heavy duty stabilizer bar



CARRYALL 232

CARRYALL 232



Run circles around the big boys.

Whoever said you can't be strong and nimble at the same time never met the Carryall 232. This mighty mite in the Club Car® line packs a whole lot of muscle in a smaller package. It can handle a total capacity of 800 pounds without breaking a sweat, while at the same time executing the tightest turning radius in its class. Which means there aren't many tight spots that the Carryall 232 can't get out of, and a lot of chores in hard-to-reach places on the course just got easier.

- Choice of gas or electric powertrain
- 800 lb/363.2 kg total vehicle capacity
- Generous 7.1 ft³/0.2 m³, 300 lb/136.1 kg bed box capacity
- Lightweight, rust-proof aluminum frame
- Durable, corrosion-resistant, composite bed box
- Scratch and impact resistant ABS Plastic front and ArmorFlex® rear body
- Self-adjusting rack & pinion steering
- Self-adjusting rear mechanical drum brakes with foot-operated park brake
- Smooth riding front and rear suspension
- Tightest turning diameter in class (17.4 ft/5.3 m)
- Greater operating range (7 gal/26.5L fuel tank)
- 2 year, 2000 hour limited warranty

CARRYALL 295

CARRYALL 295



- All-aluminum rear body
- Automatic 4WD engagement with IntelliTrak
- Rack & pinion steering
- Swing arm rear suspension with coil-over shocks
- 4-wheel hydraulic disc brakes
- Electronic fuel gauge/hour meter, low oil warning light
- Automotive style parking brake
- Full pressure, spin-on oil filter

When your utility needs
go to the next level,
**Club Car® has
the solution.**

Even when the job calls for duty at a higher level, Club Car® still has you covered. Our line of Carryall 295 vehicles are built to take on more with features like our exclusive IntelliTach™ 4-Wheel-Drive system, that automatically senses its environment and gives you power when you need it most. Or the 295 SE with four forward-facing seats and 6-point Roll Over Protective Structure (ROPS) for safety. And when you need some extra muscle, the Carryall 295 with IntelliTach™ quick-change attachment system lets you easily add attachments to handle jobs that would normally be out of the question. With a lineup this strong, the project possibilities are endless.

4x2 ACCESSORIES*



Dial up the comfort, functionality and performance of your Utility Vehicles with genuine Club Car® Accessories. We offer a complete line of factory-installed and aftermarket accessories that let you customize your utility vehicles for the chores at hand. Want to keep working regardless of the weather, operate on tougher terrain, pull more, haul more or demand longer hours of service from your vehicles? Club Car has the accessories to get it done.

Get More Done With Genuine Club Car® Accessories



Canopy Top



Heavy-Duty Front Bumper



Flatbed Tool Box



Cargo Box Tool Box



Driving Range Protective Enclosure



Universal Ball Picker Mount



ROPS Cab (Roll Over Protective Structure)



Cab Safety Strobe Light



Cab Outside Mirrors



Halogen Work Lights



Accessory Switch-Panel



Cab Fan Defogger



Hour Meter



Fuel Gauge/ Hour Meter



Heavy-Duty Batteries



Battery Capacity Indicator



On-Board Charger



Cab Heater



Van Box



1,700 lb. Winch



2,500 lb. Winch



Nerf Bars



Stake-side Kit



Swisher® Dump Cart



Electric Bed Lift



Trailer Hitch



2-Inch Front Receiver Hitch



2-Inch Rear Receiver Hitch



Wheel Cover



Premium Tread 4-Ply or 6-Ply Tires



Extra-Traction, 6-Ply Tires



Turf Tires



All-Terrain Tires



Mud Tires

* For a complete listing of accessories, please contact your local Club Car dealer.

4x2 SPECIFICATIONS

| POWER SOURCE | TURF 1 | | TURF 2 | |
|-----------------------------|---|---|---|---|
| | ELECTRIC | GASOLINE | ELECTRIC | GASOLINE |
| ENGINE | N/A | Kawasaki 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter | N/A | Kawasaki 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter |
| DRIVE MOTOR | 48-volt shunt sepex | N/A | 48-volt shunt/sepex | N/A |
| HORSEPOWER | 3.2 hp @ 2,400 rpm (continuous), 10 hp @ 1,125 rpm (intermittent) | 11.5 hp @ 3,600 rpm, exceeds SAE J1940 Performance Standards | 3.1 hp @ 3,400 rpm (continuous), 21 hp @ 2,000 rpm (intermittent) | 11.5 hp @ 3,600 rpm, exceeds SAE J1940 Performance Standards |
| GOVERNOR | N/A | Automatic ground speed sensing, internally geared-in unitized transaxle | N/A | Automatic ground speed sensing |
| GOVERNED RPM | N/A | 3,050 +/- 30 | N/A | 3,170 +/- 30 |
| IGNITION | N/A | Electronic with electronic limiter | N/A | Electronic with electronic limiter |
| DRIVE UNIT | 12.3:1 direct-drive axle, double-reduction helical gear | Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse | 12.3:1 direct-drive axle, double-reduction helical gear | Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse |
| ELECTRICAL SYSTEM | 48-volt | 12-volt, 500 cca 105 min reserve | 48-volt | 12-volt, 500 CCA, 105 min. reserve |
| BATTERIES | Six 8-volt 117 min @ 56 amp | N/A | Eight 6-volt standard: T105 115 min @ 75 amps; heavy-duty T145 145 min @ 745 amps | N/A |
| CHARGER | Automatic 48-volt DC, 17 amp, UL and CUL listed | N/A | Automatic 48-volt DC, 17 amp, UL and CUL listed | N/A |
| CONTROLLER | 250A solid state | N/A | 500A solid state | N/A |
| KEY-OR PEDAL-START | Pedal | Pedal | Pedal | Pedal |
| STEERING | Self-adjusting rack and pinion | Self-adjusting rack and pinion | Self-adjusting rack and pinion | Self-adjusting rack and pinion |
| FRONT SUSPENSION | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks |
| BRAKES | Self-adjusting rear mechanical drum | Self-adjusting rear mechanical drum | 4-wheel mechanical drum | 4-wheel mechanical drum |
| PARK BRAKE | Foot-operated, multi-lock | Foot-operated, multi-lock | Foot-operated, multi-lock | Foot-operated, multi-lock |
| FRAME/CHASSIS | Aluminum I-beam | Aluminum I-beam | Aluminum I-beam | Aluminum I-beam |
| FRONT BODY | ArmorFlex® | ArmorFlex® | ArmorFlex® | ArmorFlex® |
| REAR BODY | All aluminum | All aluminum | All aluminum | All aluminum |
| TIRES | 18 x 8.50-8, 4-ply rated, premium tread | 18 x 8.50-8, 4-ply rated, premium tread | 18 x 8.50-8, 6-ply rated, premium tread | 18 x 8.50-8, 6-ply rated, premium tread |
| INSTRUMENTATION | Battery warning light | Electronic fuel gauge/hour meter, low-oil warning light | Battery warning light | Electronic fuel gauge/hour meter, low oil warning light |
| CARGO BOX SIZE | 37.6 in x 45.1 in x 9.3 in (9.1 ft) 95.6 cm x 114.6 cm x 23.5 cm | 37.6 in x 45.1 in x 9.3 in (9.1 ft) 95.6 cm x 114.6 cm x 23.5 cm | 48.8 in x 49.8 in x 10.9 in (15.3 ft) 123.8 cm x 126.4 cm x 27.6 cm | 48.8 in x 49.8 in x 10.9 in (15.3 ft) 123.8 cm x 126.4 cm x 27.6 cm |
| FLAT BED SIZE | 35.8 in x 44.3 in (90.8 cm x 112.4 cm) | 35.8 in x 44.3 in (90.8 cm x 112.4 cm) | 46.9 in x 48.3 in (119.1 cm x 122.7 cm) | 46.9 in x 48.3 in (119.1 cm x 122.7 cm) |
| BED HEIGHT | 27.5 in (69.9 cm) | 27.5 in (69.9 cm) | 27.5 in (69.9 cm) | 27.5 in (69.9 cm) |
| BED CAPACITY | 300 lb (136.1 kg) | 300 lb (136.1 kg) | 800 lb (362.9 kg) | 800 lb (362.9 kg) |
| TOTAL VEHICLE CAPACITY | 800 lb (363.2 kg) | 800 lb (363.2 kg) | 1,200 lb (544.8 kg) | 1,200 lb (544.8 kg) |
| OVERALL LENGTH | 103.5 in (262.9 cm) | 103.5 in (262.9 cm) | 111 in (281.9 cm) | 111 in (281.9 cm) |
| OVERALL WIDTH | 48 in (121.9 cm) | 48 in (121.9 cm) | 50 in (127 cm) | 50 in (127 cm) |
| OVERALL HEIGHT | 48 in (121.9 cm) | 48 in (121.9 cm) | 48 in (121.9 cm) | 48 in (121.9 cm) |
| WHEELBASE | 65.5 in (166.4 cm) | 65.5 in (166.4 cm) | 77.5 in (196.9 cm) | 77.5 in (196.9 cm) |
| GROUND CLEARANCE | 4.5 in (11.4 cm) | 4.5 in (11.4 cm) | 4.5 in (11.4 cm) | 4.5 in (11.4 cm) |
| FUEL TANK CAPACITY | N/A | 5.1 gal (19.2L) | N/A | 5.1 gal (19.2L) |
| STABILIZER BAR | No | Yes | No | Yes |
| TREAD | 34.5 in/38.5 in (87.6 cm/97.8 cm) | 34.5 in/38.5 in (87.6 cm/97.8 cm) | 34.5 in/38.5 in (87.6 cm/97.8 cm) | 34.5 in/38.5 in (87.6 cm/97.8 cm) |
| DRY WEIGHT (LESS BATTERIES) | 530 lb (240.6 kg) | 658 lb (298.7 kg) | 612 lb (277.8 kg) | 724 lb (328.7 kg) |
| OUTSIDE RADIUS CIRCLE | 17.5 ft (5.3 m) dia | 17.5 ft (5.3 m) dia | 20.7 ft (6.3 m) dia | 20.7 ft (6.3 m) dia |
| TURNING RADIUS | 8.4 ft (2.6 m) | 8.4 ft (2.6 m) | 10 ft (3 m) | 10 ft (3 m) |
| SPEED RANGE | 12-15 mph (19.3-24.1 kph) | 12-15 mph (19.3-24.1 kph) | 5-17 mph (8-27.3 kph) | 14-16 mph (22.5-25.7 kph) |
| VEHICLE WARRANTY | 2-year, limited; 4-year batteries | 2-year, limited | 2-year, limited; 4-year batteries | 2-year, limited |

* There are no warranties, express or implied, contained herein. See Limited Warranty found in the owner's manual or write to Club Car, Inc. The company reserves the right to make design changes without obligation to make these changes on units previously sold. These vehicles are designed and manufactured for off-road use only. They do not conform to Federal Motor Vehicle Safety Standards for automobiles or to FMVSS 500 for low-speed vehicles, and are not equipped for operation on public streets, roads or highways.

4x2 SPECIFICATIONS

| POWER SOURCE | TURF 6 | TURF 252 WITH IQ PLUS™ | TURF 252 | CARRVALL 232 | |
|-----------------------------|---|--|---|---|---|
| | GASOLINE | ELECTRIC | GASOLINE | ELECTRIC | GASOLINE |
| ENGINE | Kawasaki 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter | N/A | Kawasaki 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter | N/A | Kawasaki 286 cc |
| DRIVE MOTOR | N/A | 48-volt shunt/sepex | N/A | 48-volt | N/A |
| HORSEPOWER | 11.5 hp @ 3,600 rpm, exceeds SAE J1940 Performance Standards | 3.7 hp @ 3,400 rpm (continuous) 21 hp @ 2,000 rpm (peak) | 11.5 hp @ 3,600 rpm, exceeds SAE J1940 Performance Standards | 3.2 hp (continuous)/10 hp (intermittent) | 9.5 hp @ 3,600 rpm, exceeds SAE J1940 Performance Standards |
| GOVERNOR | Automatic ground speed sensing, internally geared-in unitized transaxle | N/A | Automatic ground speed sensing, internally geared-in unitized transaxle | N/A | Automatic ground speed sensing, internally geared-in unitized transaxle |
| GOVERNED RPM | N/A | 3,050 +/- 30 | N/A | 2,900 +/- 30 | 3,300 +/- 30 |
| IGNITION | Electronic with electronic RPM limiter | N/A | Electronic with electronic limiter | N/A | Electronic w/electronic RPM limiter |
| DRIVE UNIT | Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse | 12.3:1 direct-drive axle, double-reduction helical gear | Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse | 12.3:1 direct-drive axle, double-reduction helical gear | Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse |
| ELECTRICAL SYSTEM | 12-volt, 500 cca 105 min reserve | 12-volt, 500 cca 105 min reserve | 48-volt | 12-volt, 500 cca 105 min reserve | 48-volt |
| BATTERIES | N/A | Eight 6-volt; Standard: T105 = 115 min @ 75 amps; Heavy Duty: T145 = 145 min @ 75 amps | N/A | Six 8-volt | N/A |
| CHARGER | N/A | Automatic, computer-controlled 48-volt DC, 17 amp, UL and CUL listed | N/A | 48-volt variable with on-board computer | N/A |
| CONTROLLER | N/A | 500A solid state | N/A | 250 amp solid state | N/A |
| KEY-OR PEDAL-START | Key | Pedal | Pedal | Pedal | Pedal |
| STEERING | Self-adjusting rack and pinion | Self-adjusting rack and pinion | Self-adjusting rack and pinion | Self-adjusting rack and pinion | Self-adjusting rack and pinion |
| FRONT SUSPENSION | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks | Independent leaf spring with dual hydraulic shocks |
| BRAKES | 4-wheel mechanical drum | 4-wheel, mechanical drum | 4-wheel, mechanical drum | Rear-wheel, mechanical drum | Rear-wheel, mechanical drum |
| PARK BRAKE | Foot-operated, multi-lock | Foot-operated, multi-lock | Foot-operated, multi-lock | Foot-operated | Foot-operated |
| FRAME/CHASSIS | Aluminum I-beam | Aluminum I-beam | Aluminum I-beam | Aluminum I-beam | Aluminum I-beam |
| FRONT BODY | ArmorFlex® | ArmorFlex® | ArmorFlex® | ArmorFlex® | ArmorFlex® |
| REAR BODY | All aluminum | All aluminum | All aluminum | ABS plastic | ABS plastic |
| TIRES | 18 x 6.50-8, 6-ply rated, premium tread | 22 x 11-10, 6 ply rated, heavy-duty all-terrain tread | 18 x 6.50-8, 6-ply rated, premium tread | 22 x 11-10, 8 ply rated, heavy-duty all-terrain tread | 20 x 10-8, 4-ply rated |
| INSTRUMENTATION | Electronic fuel gauge/hour meter, low-oil warning light | Electronic fuel gauge/hour meter, low-oil warning light | Electronic fuel gauge/hour meter, low-oil warning light | Electronic fuel gauge/hour meter, low-oil warning light | Electronic fuel gauge/hour meter, low-oil warning light |
| CARGO BOX SIZE | 70.5 in x 45.1 in x 9.3 in (17.1 ft) 179.1 cm x 114.6 cm x 23.5 cm | 48.4 in x 49.8 in x 10.9 in (123.8 cm x 126.4 cm x 27.6 cm) | 70.5 in x 45.1 in x 9.3 in (17.1 ft) 179.1 cm x 114.6 cm x 23.5 cm | 48.4 in x 49.8 in x 10.9 in (123.8 cm x 126.4 cm x 27.6 cm) | 27.5 in x 43.5 in x 11 in (65.3 cm x 110.5 cm x 27.9 cm) |
| FLAT BED SIZE | 67.6 in x 44.2 in (171.8 cm x 112.2 cm) | 46.9 in x 48.3 in (119.1 cm x 122.7 cm) | 67.6 in x 44.2 in (171.8 cm x 112.2 cm) | 46.9 in x 48.3 in (119.1 cm x 122.7 cm) | N/A |
| BED HEIGHT | 27 in (68.6 cm) | 29.8 in (75.6 cm) | 27 in (68.6 cm) | 29.8 in (75.6 cm) | 28.75"/73cm |
| BED CAPACITY | 1,000 lb (499.4 kg) | 500 lb (226.8 kg) | 1,000 lb (499.4 kg) | 500 lb (226.8 kg) | 300 lb (136.1 kg) |
| TOTAL VEHICLE CAPACITY | 1,500 lb (681 kg) | 900 lb (408.2 kg) | 1,500 lb (681 kg) | 900 lb (408.2 kg) | 800 lb (363.2 kg) |
| OVERALL LENGTH | 134 in (340.4 cm) | 120.4 in (305.8 cm) | 134 in (340.4 cm) | 120.4 in (305.8 cm) | 100.5 in (255.3 cm) |
| OVERALL WIDTH | 49.3 in (125.2 cm) | 51.3 in (130.2 cm) | 49.3 in (125.2 cm) | 51.3 in (130.2 cm) | 49.5 in (125.7 cm) |
| OVERALL HEIGHT | 48 in (121.9 cm) | 51.1 in (129.8 cm) | 48 in (121.9 cm) | 51.1 in (129.8 cm) | 48 in (121.9 cm) |
| WHEELBASE | 98.5 in (250.2 cm) | 78.5 in (199.4 cm) | 98.5 in (250.2 cm) | 78.5 in (199.4 cm) | 65 in (165.1 cm) |
| GROUND CLEARANCE | 4.5 in (11.4 cm) | 6.4 in (16.3 cm) | 4.5 in (11.4 cm) | 6.4 in (16.3 cm) | 5.5 in (14 cm) |
| FUEL TANK CAPACITY | 5.1 gal (19.2L) | N/A | 5.1 gal (19.2L) | 5.1 gal (19.2L) | N/A |
| STABILIZER BAR | Yes | No | Yes | Yes | N/A |
| TREAD | 34.5 in/38.6 in (87.6 cm/97.8 cm) | 36.5 in/41.3 in (92.7 cm/104.8 cm) | 34.5 in/38.6 in (87.6 cm/97.8 cm) | 36.5 in/41.3 in (92.7 cm/104.8 cm) | 34/38 in (86.4/96.5 cm) |
| DRY WEIGHT (LESS BATTERIES) | 868 lb (394.1 kg) | 900 lb (408.2 kg) | 868 lb (394.1 kg) | 910 lb (412.8 kg) | 781 lb (354.3 kg) |
| OUTSIDE RADIUS CIRCLE | 24.7 ft (7.5 m) dia | 21.7 ft (6.6 m) dia | 24.7 ft (7.5 m) dia | 21.7 ft (6.6 m) dia | - |
| TURNING RADIUS | 12 ft (3.7 m) | 10.8 ft (3.3 m) | 12 ft (3.7 m) | 10.8 ft (3.3 m) | 8.75 ft (2.7 m) |
| SPEED RANGE | 14-16 mph (22.5-25.7 kph) | 15-17 mph (24.1-27.4 kph) | 14-16 mph (22.5-25.7 kph) | 15-17 mph (24.1-27.4 kph) | 17-19 mph (27.4-30.6 kph) |
| VEHICLE WARRANTY | 2-year, limited | 2-year, limited; 4-year batteries | 2-year, limited | 2-year, limited | 2-year, limited |

* There are no warranties, express or implied, contained herein. See Limited Warranty found in the owner's manual or write to Club Car, Inc. The company reserves the right to make design changes without obligation to make these changes on units previously sold. These vehicles are designed and manufactured for off-road use only. They do not conform to Federal Motor Vehicle Safety Standards for automobiles or to FMVSS 500 for low-speed vehicles, and are not equipped for operation on public streets, roads or highways.

4x4 ACCESSORIES*

Set Your 4x4 Vehicles On Maximum Performance



Club Car® 4x4 Utility Vehicles are as sophisticated and branny as they come, and you can get even more performance when you outfit with genuine Club Car accessories. Built tough for the most demanding jobs, Club Car accessories maximize the versatility of your 4x4s. From towing packages and winches to innovative storage and hauling solutions, Club Car accessories let you rig your 4x4 Utility Vehicles to handle the toughest jobs on the course.



Custom Van Box



Rear Cargo Cage



Electric Bed Lift




Underhood Storage (Gas Only)



Stake-Side Kit



2-Inch Front Receiver Hitch



Cargo Bed Toolbox



2,500 lb. Warn Winch



Pintle Hitch



Nerf Bars



54- or 62-Inch Plow Blade



Swisher Trailmower



Swisher Dump Cart



40-Gallon Sprayer



Cab Heater (Gas Only)

* For a complete listing of accessories, please contact your local Club Car dealer.



Lighting Package (includes horn, turn signals and brake lights)



Plastic Canopy Top

4x4 SPECIFICATIONS

| | CARRYALL 295 | | CARRYALL 295 SE | | CARRYALL 295 INTELLITACH™ |
|--|--|--|--|--|--|
| | GASOLINE | DIESEL | GASOLINE | DIESEL | DIESEL |
| POWER SOURCE | Kawasaki 4-cytle, OHV, 675 cc, twin-cylinder industrial grade | Kubota D722, 719 cc, 3-cylinder | Kawasaki 4-cytle, OHV, 651 cc, twin-cylinder industrial grade | Kubota D722, 719 cc, 3-cylinder | Kubota D722, 719 cc, 3-cylinder industrial grade |
| ENGINE | Liquid | Liquid | Liquid | Liquid | Liquid |
| ENGINE-COOLING | Air | Air | Air | Air | Air |
| ENGINE-LUBRICATION AND OIL FILTER TYPE | Full-pressure, spin-on |
| MAXIMUM TORQUE | 39.8 ft-lb (54.9 Nm) | 33 ft-lb (44.7 Nm) | 39.8 ft-lb (54.9 Nm) | 33 ft-lb (44.7 Nm) | 33 ft-lb (44.7 Nm) |
| HORSEPOWER | 23 hp (17.2 kw) | 20 hp (14.9 kw) | 23 hp (17.2 kw) | 20 hp (14.9 kw) | 20 hp (14.9 kw) |
| IGNITION | Transistorized magneto | Compression | Transistorized magneto | Compression | Compression |
| 4WD ENGAGEMENT | Automatic - IntelliTrak |
| FRONT DIFFERENTIAL | Automatic - IntelliTrak |
| REAR DIFFERENTIAL | Auto locking - IntelliTrak |
| TORQUE CONVERTER | CVT | CVT | CVT | CVT | CVT |
| ELECTRICAL SYSTEM | 12-volt, 500 CCA |
| STEERING | Rack and pinion |
| TILT STEERING WHEEL | Standard | Standard | Standard | Standard | Standard |
| FRONT SUSPENSION | Independent double A-arms with coil-over shocks |
| REAR SUSPENSION | Swing arm with coil-over shocks |
| BRAKES | 4-wheel, hydraulic disc |
| PARK BRAKE | Automotive style |
| FRAME/CHASSIS | Tubular aluminum |
| FRONT BODY | GE Geloy high-impact, scratch-resistant, injection molded color |
| REAR BODY | All aluminum |
| FRONT TIRES | All-terrain, 25 x 10.5-12, 4-ply |
| REAR TIRES | All-terrain, 25 x 10.5-12, 4-ply |
| INSTRUMENTATION | Electronic fuel gauge/hour meter, low oil warning light | Electronic fuel gauge/hour meter, low oil warning light, coolant high temp warning light | Electronic fuel gauge/hour meter, low oil warning light | Electronic fuel gauge/hour meter, low oil warning light, coolant high temp warning light | Electronic fuel gauge/hour meter, seatbelt warning light, low oil warning light, coolant high-temp warning light |
| FLAT BED SIZE | 48.8 in x 49.8 in x 10.9 in (124 cm x 126.5 cm x 27.7 cm) | 48.8 in x 49.8 in x 10.9 in (124 cm x 126.5 cm x 27.7 cm) | 48.8 in x 49.8 in x 10.9 in (124 cm x 126.5 cm x 27.7 cm) | 48.8 in x 49.8 in x 10.9 in (124 cm x 126.5 cm x 27.7 cm) | 48.8 in x 49.8 in x 10.9 in (123.8 cm x 126.4 cm x 27.6 cm) |
| BED HEIGHT | 33 in (83.8 cm) |
| BED CAPACITY | 800 lb (363.2 kg); 1,050 lb (476.3 kg) available | 800 lb (363.2 kg) |
| TOTAL VEHICLE CAPACITY | 1,200 lb (544.3 kg); 1,450 lb (657.7 kg) available | 1,200 lb (544.8 kg); 1,450 lb (657.7 kg) available | 1,600 lb (725.8 kg) | 1,400 lb (635.0 kg) | 1,700 lb (771.1 kg) |
| SEATING | Choice of bucket or bench; Adjustable driver's seat only available with bucket seat option | Choice of bucket or bench; Adjustable driver's seat only available with bucket seat option | Choice of bucket or bench; Adjustable driver's seat only available with bucket seat option | Choice of bucket or bench; Adjustable driver's seat only available with bucket seat option | Bench Seats with adjustable driver's seat |
| SEATING CAPACITY | 2 | 2 | 4 | 4 | 2 |
| OVERALL LENGTH | 124.6 in (316.5 cm) | 124.6 in (316.5 cm) | 157.6 in (400.3 cm) | 157.6 in (400.3 cm) | 148.6 in (377.4 cm) |
| OVERALL WIDTH | 60 in (152.4 cm) |
| OVERALL HEIGHT | 78.6 in (199.6 cm) |
| WHEELBASE | 88.7 in (225.3 cm) | 88.7 in (225.3 cm) | 114 in (225.3 cm) | 114 in (225.3 cm) | 81.5 in (225.3 cm) |
| GROUND CLEARANCE | 7.4 in (18.8 cm) |
| FUEL TANK CAPACITY | 6.5 gallons (24.6 L) |
| TREAD | 48.8 in (124 cm) |
| DRY WEIGHT (LESS BATTERIES) | 1,430 lb (648.4 kg) | 1,559 lb (707.2 kg) | 1,605 lb (728 kg) | 1,786 lb (810.1 kg) | 1,709 lb (775.1 kg) |
| MAXIMUM SPEED | 25 mph (40.2 kph) |
| TURNING RADIUS | 13 ft (3.8 m) | 13 ft (3.8 m) | 17 ft (5.4 m) | 17 ft (5.4 m) | 13.8 ft (4.2 m) |
| VEHICLE WARRANTY | 2-year, limited |

* There are no warranties, express or implied, contained herein. See Limited Warranty found in the owner's manual or write to Club Car, Inc. The company reserves the right to make design changes without obligation to make these changes on units previously sold. These vehicles are designed and manufactured for off-road use only. They do not conform to Federal Motor Vehicle Safety Standards for automobiles or to FMVSS 500 for low-speed vehicles, and are not equipped for operation on public streets, roads or highways.



The business of better utility vehicles,
that's Club Car's® Turf Line.

Around the world, the Club Car® name is recognized for the highest levels of performance and quality. We are just as proud of our reputation for helping our customers find solutions that advance their businesses. Nowhere are those solutions more apparent than in our line of utility vehicles for today's golf operations. Through technology, innovation and uncompromising attention to build quality, Club Car is delivering golf's best turf utility vehicles.

We like to think our standing in the industry is a direct result of the high regard we have for the game of golf, and for those who make their livings around it. That regard is reflected in our promise of unmatched performance and unequaled service. No one in the industry invests more in relationships, research, design, engineering, materials and craftsmanship. That's why no one else is Club Car.

Let's talk about putting the finest utility vehicles to work for you.
Call us at 1.800.CLUBCAR • +1 706.863.3000, or visit us on the web at clubcar.com.



Ingersoll Rand is a global diversified firm providing products, services and solutions to enhance the quality and comfort of air in homes and buildings, transport and protect food and perishables, secure homes and commercial properties, and increase industrial productivity and efficiency. Driven by a 100-year-old tradition of technological innovation, we enable our customers to create progress and a positive impact in their world.

Please note vehicles contained throughout the brochure may be shown with additional accessories.

1.800.CLUBCAR • +1 706.863.3000

www.clubcar.com

www.ingersollrand.com

01/10 58648767